

Acrylic Texture Coating

Interior/Exterior - White Base



CC5501 . Medium Finish
CC5502 . Sand Finish
CC5503 . Coarse Finish

PRODUCT INFORMATION

Colorcraft Acrylic Texture Coating is specifically designed to provide a textured finish on properly Interior and exterior surfaces. this product helps minimize defects and irregularities found on concrete and masonry surfaces. It also provides a mildew resistant on the paint film. Not for use on floors, below-grade surfaces and areas subject to hydrostatic pressure.

RECOMMENDED USES:

Use on properly prepared, primed or previously painted exterior surfaces.

• Stucco • Concrete • Masonry • Concrete Masonry Units • Brick • Fiber Cement

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. PR710 White Base 620 fl oz / 30 fl oz (5-gallon)

Gloss: 0 – 5 @ 60°

Resin Type: Acrylic

Weight per Gallon: 10.3 lb

% Solids by Volume: 43 ± 2%

% Solids by Weight: 52 ± 2%

VOC: < 50 g/L

Flash Point: N/A

Viscosity: 118 – 127 KU

Recommended Film Thickness:

Wet: 13.8 mils / Dry: 5.9 mils @ 50 sq ft/gal

Wet: 8.6 mils / Dry: 3.7 mils @ 80 sq ft/gal

Coverage: 50 – 80 sq ft/gal depending on the surface texture, porosity and application method. Does not include the loss of material from spraying. Film thickness depends on porosity and various substrate irregularities.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/4" – 1 1/4" nap roller cover

Texture Sprayer: Graco President 10:1 Air Spray System, Graco Texspray RTX 5500PX, or similar texture spray equipment capable of spraying up to 3 mm aggregate size

Tip: 8mm – 12mm

Thinning: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to one quart of water per 5 gallons of coating.

NOTE: For best results, it is recommended to apply by spray equipment that is specifically designed for aggregate coatings. Texture appearance is controlled by orifice size, pressure, film thickness and application technique. A double pass provides best uniformity. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Dry Time: @ 77°F & 50% RH

To Touch: 1 hour

To Recoat: 2 hours

Dry times are temperature, humidity and film thickness dependent.

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

New Masonry: The pH must be 10 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth trowel concrete, create an adequate profile for adhesion using a product such as muriatic acid etcher or with mechanical means. Remove all loose aggregate and debris. Prime the area with an alkali-resistant primer.

Stain-Blocking: After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before topcoating the entire area. If bleeding continues, primer may need a longer dry time before applying topcoat.

Previously Painted Surfaces: Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust. Fill all gaps with a suitable sealant, and allow to completely dry prior to coating.

COMPLIES WITH THE BELOW AS OF 12/1/2021

SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
CARB	YES	AIM	YES
OTC PHASE II	YES	MPI#	42

Glossy Surfaces: For maximum adhesion, sand the surface thoroughly to provide a rough surface before coating.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

ACRYLIC TEXTURE COATING

Exterior - White Base



CC5501 . Medium Finish

PERFORMANCE DATA:

Resistance to Wind-Driven Rain (ASTM D6904):

Result: Pass

Substrate: Patio Block/Standard CMU Cap Coating

System tested:

System #1

Primer: ColorCraft ProCraft Primer & Sealer CC3850-
One (1) coat at 400sq ft/gal (1.8 mils DFT)

Topcoat: ColorCraft Acrylic Texture Coating at 50 sq
ft/gal (1.8 mils DFT)

System #2

Primer: ColorCraft ProCraft Primer & Sealer CC3850-
One (1) coat at 400 sq ft/gal (1.8 mils DFT)

Intermediate: ColorCraft Acrylic Texture Coating at 50 sq
ft/gal (1.8 mils DFT)

Topcoat: ColorCraft ProCraft Int/Ext Paint- one (1) coat
at 250 sq ft/gal (2.1 mils DFT)

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Not for use on below-grade substrates. Will not withstand hydrostatic pressure.
- Not for use on horizontal surfaces (floors, roofs, decks, etc.) where water will collect.
- Not for use on overhead horizontal surfaces (undersides of balconies, soffits, etc.)
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Do not apply in direct sunlight. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 35°F can inhibit proper film formation.
- Allow 4 weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

WARNING CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS: PUMICE AND CRYSTALLINE SILICA. Avoid contact with skin and eyes and avoid breathing vapor or spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

COLORCRAFT PAINT LLC BELIEVES THE TECHNICAL DATA REPRESENTED IN THIS TECHNICAL BULLETIN TO BE CURRENT AS OF THE DATE OF PUBLICATION.

ColorCraft Paints, LLC

10160 NW South River Dr. | Medley, Florida 33178
954.899.8971 | sales@cocraft.net | colorcraftpaints.com